

COOLING																		
Model	Indoor																	
	DB	WB		5F (-15C)	15F (-9.4C)	25F (-3.9C)	35F (1.7C)	45F (7.2C)	55F (12.8C)	65F (18.3C)	75F (23.9C)	85F (29.4C)	95F (35C)	105F (40.6C)	109.4F (43C)	115F (46.1C)	122F (50C)	122F (50C)
DM36HIDU230X5 DM36HOS18230E5 Ducted 208/230	65F (18.3C)	54F	TC	32.24	32.47	32.70	32.93	33.16	33.39	33.21	33.03	33.49	30.10	25.91	23.81	21.72	17.53	7.48
			SC	23.11	23.47	23.83	24.19	24.55	24.91	24.96	25.01	26.22	24.74	22.84	20.26	17.68	13.38	6.66
	70F (21.1C)	59F	TC	33.07	33.30	33.53	33.76	33.99	34.22	33.52	33.83	34.35	31.88	26.58	24.43	22.28	18.98	7.78
			SC	23.62	23.98	24.34	24.70	25.06	25.42	25.47	25.53	26.76	25.25	23.31	20.68	18.05	13.66	6.92
	75F (23.9C)	63F	TC	33.91	34.15	34.39	34.63	34.87	35.11	34.75	34.39	35.02	34.31	29.38	26.76	24.45	19.82	8.16
			SC	24.18	24.56	24.94	25.32	25.70	26.08	26.20	26.33	27.54	26.22	24.37	21.56	18.75	14.20	7.26
	80F (26.7C)	67F	TC	34.98	35.39	35.80	36.21	36.62	37.03	36.99	36.95	36.70	36.55	32.59	29.11	26.63	21.67	8.55
			SC	24.61	25.04	25.47	25.90	26.33	26.76	26.94	27.12	27.31	27.19	25.43	22.43	19.44	14.74	7.61
DM48HIDU230X5 DM48HOS18230E5 Ducted 208/230	65F (18.3C)	54F	TC	45.33	45.52	45.66	45.81	45.95	46.09	45.77	45.16	43.86	41.17	34.55	31.47	28.53	25.45	7.48
			SC	32.96	33.12	33.28	33.43	33.59	33.89	33.44	33.21	32.25	31.83	29.46	27.09	24.63	22.21	6.66
	70F (21.1C)	59F	TC	46.33	46.48	46.63	46.78	47.22	47.37	46.75	46.28	45.12	42.19	35.40	32.28	29.35	26.07	7.78
			SC	33.38	33.74	33.90	34.06	34.60	34.79	34.34	33.88	32.90	32.48	30.09	27.58	25.24	22.68	6.92
	75F (23.9C)	63F	TC	46.74	46.99	47.72	47.97	48.22	48.46	47.90	47.63	47.13	44.98	37.09	34.19	31.31	28.46	8.16
			SC	33.99	34.23	34.46	34.70	35.14	35.38	34.97	34.94	34.61	34.64	31.69	29.40	27.09	24.74	7.26
	80F (26.7C)	67F	TC	47.94	48.25	48.55	49.00	49.46	49.76	49.65	49.04	48.35	48.29	40.82	35.55	33.60	30.90	8.55
			SC	34.32	34.45	34.57	34.70	35.11	35.24	34.47	33.70	33.84	33.61	30.92	29.38	27.72	26.27	7.61

DB: Dry Bulb - WB: Wet Bulb - TC: Total Net Capacity (1000 BTU/hour) - SC: Sensible Capacity (1000 BTU/hour) - Input: Total Power (kW)

HEATING												
Model	Indoor											
	DB		17F (-8.3C)	19.4F (-7C)	24.8F (-4C)	32F (0C)	35F (1.7C)	39.2F (4C)	44.6F (7C)	47F (8.3C)	53.6F (12C)	57F (13.9C)
DM36HIDU230X5 DM36HOS18230E5	55F (15.6C)	TC	30.96	31.98	33.40	38.37	39.65	44.00	46.10	46.55	46.99	47.45
		Input	3.77	3.69	3.76	3.37	3.43	3.64	4.16	3.89	3.61	3.36
	60F (15.6C)	TC	29.82	31.17	32.26	36.49	38.54	42.59	45.37	45.66	45.94	46.23
		Input	3.87	3.83	3.92	3.51	3.64	3.77	4.30	4.04	3.77	3.53
	65F (18.3C)	TC	28.71	30.39	31.15	34.71	37.46	41.21	44.65	44.78	44.92	45.05
		Input	3.97	3.98	4.09	3.82	3.86	3.91	4.45	4.19	3.94	3.70
	70F (21.1C)	TC	28.37	29.13	29.71	33.32	36.82	40.31	43.28	43.76	44.25	44.73
		Input	4.04	4.11	3.91	3.69	3.86	4.03	4.40	4.25	4.09	3.94
DM48HIDU230X5 DM48HOS18230E5	55F (15.6C)	TC	49.02	50.04	53.65	55.61	55.49	56.09	56.50	58.68	58.64	58.61
		Input	5.29	5.12	5.33	5.18	5.23	5.27	4.71	4.36	4.02	3.71
	60F (15.6C)	TC	48.28	49.40	53.18	54.87	55.15	55.63	56.04	57.40	57.16	56.92
		Input	5.45	5.21	5.52	5.40	5.44	5.48	4.93	4.56	4.20	3.87
	65F (18.3C)	TC	47.54	48.77	52.71	54.15	54.81	55.17	55.58	56.14	55.71	55.27
		Input	5.61	5.31	5.72	5.62	5.66	5.70	5.16	4.77	4.39	4.03
	70F (21.1C)	TC	46.67	47.87	51.60	53.39	54.16	54.63	55.11	55.39	54.67	53.95
		Input	5.68	5.46	5.56	5.81	5.85	5.89	5.39	4.97	4.55	4.17
	75F (23.9C)	TC	45.13	46.36	50.87	52.85	53.39	53.92	54.60	55.08	56.25	57.45
		Input	5.85	5.48	5.67	5.94	5.92	5.89	5.53	5.26	4.99	4.74

DB: Dry Bulb - WB: Wet Bulb - TC: Total Net Capacity (1000 BTU/hour) - SC: Sensible Capacity (1000 BTU/hour) - Input: Total Power (kW)

