

COOLING																						
Model	Indoor		Outdoor conditions (DB)																			
	DB	WB		-13F (-25C)	-5F (-20.6C)	-4F (-20C)	0F (-17.8C)	5F (-15C)	15F (-9.4C)	25F (-3.9C)	35F (1.7C)	45F (7.2C)	55F (12.8C)	65F (18.3C)	75F (23.9C)	85F (29.4C)	95F (35C)	105F (40.6C)	109.4F (43C)	115F (46.1C)	122F (50C)	122F (50C)
DM60HOS18230E5 DM60HIDU230X5 Ducted (208-230V)	65F (18.3C)	54F	TC	44.91	47.80	51.66	53.53	53.02	53.36	54.00	54.34	54.36	54.38	54.40	53.28	51.32	50.17	45.42	27.03	25.10	22.95	7.48
			SC	31.89	33.47	37.51	39.21	39.98	38.75	39.55	37.64	39.47	39.84	43.71	42.98	41.94	41.00	37.60	22.98	23.86	22.74	6.66
	70F (21.1C)	59F	TC	46.59	50.11	53.88	55.53	55.59	56.25	56.01	56.37	56.39	56.41	56.44	55.86	53.81	52.32	47.12	28.34	26.04	23.68	7.78
			SC	32.15	34.57	38.54	40.08	41.30	42.39	42.80	43.92	45.31	45.51	40.98	40.92	44.55	44.48	40.69	25.66	25.15	23.44	6.92
	75F (23.9C)	63F	TC	48.33	52.54	55.89	58.22	57.97	58.35	58.73	58.48	58.50	58.52	58.54	58.57	56.12	54.27	49.40	31.01	27.30	24.56	8.16
			SC	32.38	35.71	39.39	41.40	42.43	43.32	44.21	44.88	46.31	46.51	47.14	44.09	43.07	42.96	42.03	27.66	25.98	24.29	7.26
	80F (26.7C)	67F	TC	50.91	55.63	59.19	61.65	61.72	61.79	61.86	61.92	61.95	61.97	61.99	62.02	59.74	57.47	52.87	32.84	29.23	26.01	8.55
			SC	31.76	35.81	39.50	43.47	42.78	43.44	44.10	45.01	46.43	46.64	47.27	47.28	46.14	45.59	43.46	28.29	26.86	25.70	7.61

DB: Dry Bulb - WB: Wet Bulb - TC: Total Net Capacity (1000 BTU/hour) - SC: Sensible Capacity (1000 BTU/hour) - Input: Total Power (kW)

HEATING																
Model	Indoor		Outdoor conditions (DB)													
	DB		-13F (-25C)	-5F (-20.6C)	0F (-17.8C)	5F (-15C)	17F (-8.3C)	19.4F (-7C)	24.8F (-4C)	32F (0C)	35F (1.7C)	39.2F (4C)	44.6F (7C)	47F (8.3C)	53.6F (12C)	57F (13.9C)
DM60HOS18230E5 DM60HIDU230X5 Ducted (208-230V)	60F (15.6C)	TC	26.88	32.91	35.04	37.80	39.20	41.42	46.37	53.07	55.92	59.89	64.29	65.61	66.73	67.33
		Input	4.671	4.681	4.711	4.748	3.965	4.037	4.205	4.394	4.465	4.558	4.661	4.703	4.559	4.525
	65F (18.3C)	TC	26.31	32.11	34.49	36.88	38.21	40.34	45.11	51.78	54.50	58.31	62.54	64.52	65.74	66.53
		Input	4.786	4.791	4.817	4.849	4.046	4.124	4.299	4.488	4.565	4.655	4.756	4.803	4.661	4.603
	70F (21.1C)	TC	25.84	31.51	33.75	35.98	37.17	39.24	44.01	50.37	53.07	56.73	61.50	63.56	64.83	65.81
		Input	4.894	4.894	4.925	4.954	4.133	4.217	4.392	4.589	4.663	4.755	4.863	4.907	4.766	4.697
	75F (23.9C)	TC	25.04	30.57	32.77	34.98	36.17	38.06	42.73	48.91	51.58	55.19	59.65	61.72	62.95	63.77
		Input	5.021	5.026	5.063	5.077	4.244	4.331	4.515	4.704	4.789	4.888	4.995	5.044	4.885	4.824

DB: Dry Bulb - WB: Wet Bulb - TC: Total Net Capacity (1000 BTU/hour) - SC: Sensible Capacity (1000 BTU/hour) - Input: Total Power (kW)