

HEATING																	
Model	Indoor		Outdoor conditions (DB)														
	DB		-22F (-30C)	-13F (-25C)	-5F (-20.6C)	0F (-17.8C)	5F (-15C)	17F (-8.3C)	19.4F (-7C)	24.8F (-4C)	32F (0C)	35F (1.7C)	39.2F (4C)	44.6F (7C)	47F (8.3C)	53.6F (12C)	57F (13.9C)
DM09HIW23230E3 DM09HOS25230E3	60F (15.6C)	TC	7.50	8.44	9.38	10.57	11.15	12.61	12.81	13.64	14.29	14.66	15.29	15.82	16.22	17.32	17.89
		Input	1.25	1.28	1.49	1.65	1.63	1.61	1.58	1.56	1.53	1.48	1.43	1.32	1.28	1.18	1.13
	65F (18.3C)	TC	7.40	8.32	9.24	10.41	10.99	12.01	12.39	13.09	13.70	14.45	14.93	15.40	15.68	16.45	16.84
		Input	1.31	1.33	1.52	1.69	1.66	1.64	1.61	1.59	1.57	1.52	1.47	1.36	1.32	1.22	1.16
	70F (21.1C)	TC	7.29	8.20	9.11	10.26	10.83	11.40	11.97	12.53	13.10	14.24	14.56	14.98	15.14	15.57	15.79
		Input	1.35	1.38	1.55	1.72	1.70	1.67	1.65	1.62	1.60	1.55	1.50	1.39	1.35	1.25	1.20
75F (23.9C)	TC	7.18	8.07	8.97	10.11	10.67	10.79	11.54	11.98	12.51	14.03	14.20	14.56	14.60	14.70	14.75	
	Input	1.42	1.45	1.58	1.75	1.73	1.71	1.68	1.66	1.64	1.59	1.54	1.43	1.39	1.29	1.23	
DM12HIW23230E3 DM12HOS25230E3	60F (15.6C)	TC	8.32	9.36	10.40	12.09	12.46	13.58	13.72	14.33	14.52	14.66	15.29	15.82	16.22	17.32	17.89
		Input	1.58	1.71	1.75	2.04	1.96	1.88	1.80	1.72	1.64	1.48	1.43	1.32	1.28	1.18	1.13
	65F (18.3C)	TC	8.20	9.22	10.25	11.92	12.28	13.12	13.27	13.75	13.92	14.45	14.93	15.40	15.68	16.45	16.84
		Input	1.62	1.74	1.79	2.08	2.00	1.92	1.84	1.76	1.68	1.52	1.47	1.36	1.32	1.22	1.16
	70F (21.1C)	TC	8.08	9.09	10.10	11.74	12.10	12.45	12.81	13.17	13.53	14.24	14.56	14.98	15.14	15.57	15.79
		Input	1.67	1.77	1.82	2.13	2.04	1.96	1.88	1.80	1.72	1.55	1.50	1.39	1.35	1.25	1.20
75F (23.9C)	TC	7.96	8.95	9.94	11.56	11.92	11.79	12.36	12.59	13.43	14.03	14.20	14.56	14.60	14.70	14.75	
	Input	1.72	1.80	1.86	2.17	2.08	2.00	1.92	1.84	1.75	1.59	1.54	1.43	1.39	1.29	1.23	
DM18HIW23230E3 DM18HOS25230E3	60F (15.6C)	TC	11.99	15.57	18.03	18.77	19.31	20.05	20.84	21.63	22.42	24.01	24.14	24.32	25.00	26.88	27.85
		Input	2.64	2.93	3.22	3.56	3.39	3.20	3.02	2.85	2.68	2.34	2.31	2.21	2.23	2.27	2.29
	65F (18.3C)	TC	12.21	15.34	17.77	18.49	19.16	19.92	20.70	21.49	22.28	23.86	23.99	24.17	24.85	26.73	27.70
		Input	2.68	2.99	3.28	3.64	3.46	3.28	3.10	2.93	2.76	2.41	2.38	2.28	2.30	2.34	2.36
	70F (21.1C)	TC	12.42	15.11	17.51	18.22	19.00	19.79	20.57	21.35	22.14	23.71	23.84	24.02	24.70	26.58	27.55
		Input	2.71	3.05	3.35	3.71	3.53	3.36	3.18	3.01	2.83	2.48	2.45	2.35	2.37	2.41	2.43
75F (23.9C)	TC	12.64	14.89	17.25	17.95	18.85	19.66	20.44	21.22	22.00	23.56	23.69	23.87	24.55	26.43	27.40	
	Input	2.75	3.11	3.41	3.78	3.61	3.44	3.27	3.09	2.91	2.55	2.52	2.42	2.44	2.48	2.50	
DM24HIW23230E3 DM24HOS25230E3	60F (15.6C)	TC	15.20	20.13	24.24	25.49	26.34	26.66	27.55	27.82	28.13	28.30	28.89	29.79	30.36	31.92	32.72
		Input	3.19	3.62	3.93	4.24	4.34	4.20	4.38	4.44	3.94	3.72	3.71	3.28	3.26	3.22	3.20
	65F (18.3C)	TC	15.13	19.84	23.89	25.61	26.19	26.50	27.10	27.39	27.85	28.10	28.67	29.74	30.30	31.85	32.65
		Input	3.30	3.69	4.01	4.33	4.32	4.19	4.22	4.19	3.88	3.65	3.63	3.24	3.22	3.17	3.15
	70F (21.1C)	TC	15.05	19.54	23.54	25.72	26.03	26.34	26.65	26.96	27.28	27.90	28.44	29.68	30.24	31.78	32.57
		Input	3.40	3.77	4.09	4.41	4.29	4.18	4.06	3.94	3.82	3.58	3.55	3.19	3.17	3.12	3.09
75F (23.9C)	TC	14.98	19.25	23.18	25.83	25.88	26.19	26.21	26.44	27.10	27.70	28.22	29.63	30.18	31.71	32.50	
	Input	3.51	3.84	4.17	4.50	4.27	4.17	3.90	3.69	3.76	3.52	3.47	3.15	3.13	3.07	3.04	

DB: Dry Bulb - WB: Wet Bulb - TC: Total Net Capacity (1000 BTU/hour) - SC: Sensible Capacity (1000 BTU/hour) - Input: Total Power (kW)

